

COMPANY
BOLLARD
UP&DOWN
BULKHEAD
FLOODLIGHT
IN-GROUND
BRICKLIGHT
GARDEN
URBAN CLASSIC
URBAN MODERN
HIGH-BAY
POST
LAMPS
REFERENCES

LUCIA RANGE

ROUND



Round bulkhead lamp with ring, eyelid or guard cover. Made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Suitable for ceiling, wall and post installation also with bracket angled at 35°. Supplied as option with coloured backlit base. **GX53 LED** or **E27** version available. Insulation class II, Protection rating IP66.

*Plafoniera circolare con cover ad anello, a palpebra o a manubrio. Realizzata in resina antiurto stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Idonea per il montaggio a parete, a soffitto e a palo anche con braccio angolato a 35°. Disponibile anche con base per retroilluminazione colorata. Fornita nella versione a **LED GX53** o **E27**. Classe di isolamento II, grado di protezione IP66.*



1R3.000.OR1





LUCIA COMPONENTS

IP 66



COVER made of shockproof resin material, UV-rays stabilized. Ring, eyelid and grid versions available.

COVER in resina antiurto stabilizzata ai raggi UV, disponibile nella versione ad anello, a palpebra e a griglia.

Opal **DIFFUSER** made of UV-rays stabilized polymethylmethacrylate (PMMA), with silicone rubber gasket to ensure high protection against external agents.


DIFFUSORE opale realizzato in polimetilmetacrilato (PMMA) stabilizzato ai raggi UV. Completo di guarnizione in gomma siliconica per garantire un alto livello di protezione contro gli agenti esterni.

BASE made of shockproof resin material, provided with E27 or GX53 lampholder. Available in different backlit colours to create a coloured effect on wall and ceilings.

BASE realizzata in resina antiurto. Fornita completa di portalampana E27 o GX53. Disponibile in diversi colori per creare una retroilluminazione colorata su pareti e soffitti.



LUCIA



Dimensions and weight

Diameter: Ø 300 mm
Depth: 90 mm
Weight: 1 Kg

Moulded colours:

Black White Grey

Diffuser PMMA:

Opal

GX53 LED

FULLY PRE-WIRED



Bulkhead supplied **fully pre-wired** and complete with TÜV approved, long-life and efficient **GX53 LED lamp included**. Different wattage available.

- **COST SAVING:** long-life and efficient LED light sources
- **BUILT-IN DRIVER:** Quick and easy lamp replacement for a very simple maintenance after installation.

GX53 LED	W	Lm	*ADD. SUFFIX	
			Color	Suffix
	7 W	600 Lm	4000 K	.A1L
			3000 K	.A1R
	11 W	1300 Lm	4000 K	.B1L
			3000 K	.B1R
18 W	2000 Lm	4000 K	.E1L	
		3000 K	.E1R	

7W
 11W
 18W
 =
 60W
 100W
 150W
 incandescent
SAVE 90%

E27

FULLY PRE-WIRED



Bulkhead supplied **fully pre-wired** with **E27 lampholder**. White resin reflective plate designed to grant lampholder protection and isolation. Safe fixation of the electrical devices on the plate rear side.

Daylight and motion sensor available as an option. Sensor operating voltage: 220-240V (120V available on demand).

E27	max 160 mm	*ADD. SUFFIX
E27 (CFL -LED)	↔	.E27
E27 + SENSOR (CFL -LED)	📶	.ES7

POST VERSION



Lucia bulkhead range can be mounted on a pole with or without an angled bracket.

** ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE*


LED LAMPS

More technical details about TÜV approved Fumagalli LED Lamps on page 512.

LUCIA RANGE

ROUND





LUCIA E27
1R3.000.E27

Pcs 16
Kg 16,8
mc 0,194

4000K 3000K

LUCIA GX53

1R3.000.A1L	7W	1R3.000.A1R
1R3.000.B1L	11W	1R3.000.B1R
1R3.000.E1L	18W	1R3.000.E1R

GABRI/ LUCIA 1L
1R3.613.010

Pcs 1
Kg 4
mc 0,097

300 240

1000

Ø 240

GABRI/ LUCIA 2L
1R3.613.020

Pcs 1
Kg 5
mc 0,097

300 240

1000

Ø 240

MINIGABRI/ LUCIA 1L
1R3.612.010

Pcs 1
Kg 3,5
mc 0,065

300 240

750

Ø 240

MINIGABRI/ LUCIA 2L
1R3.612.020

Pcs 1
Kg 4,5
mc 0,065

300 240

750

Ø 240

LUCIA-EL E27
2R3.000.E27

Pcs 16
Kg 16,8
mc 0,194

4000K 3000K

LUCIA-EL GX53

2R3.000.A1L	7W	2R3.000.A1R
2R3.000.B1L	11W	2R3.000.B1R
2R3.000.E1L	18W	2R3.000.E1R

GABRI/ LUCIA-EL 1L
2R3.613.010

Pcs 1
Kg 4
mc 0,097

300 240

1000

Ø 240

GABRI/ LUCIA-EL 2L
2R3.613.020

Pcs 1
Kg 5
mc 0,097

300 240

1000

Ø 240

MINIGABRI/ LUCIA-EL 1L
2R3.612.010

Pcs 1
Kg 3,5
mc 0,065

300 240

750

Ø 240

MINIGABRI/ LUCIA-EL 2L
2R3.612.020

Pcs 1
Kg 4,5
mc 0,065

300 240

750

Ø 240

LUCIA-GD E27
3R3.000.E27

Pcs 16
Kg 16,8
mc 0,194

4000K 3000K

LUCIA-GD GX53

3R3.000.A1L	7W	3R3.000.A1R
3R3.000.B1L	11W	3R3.000.B1R
3R3.000.E1L	18W	3R3.000.E1R

GABRI/ LUCIA-GD 1L
3R3.613.010

Pcs 1
Kg 4
mc 0,097

300 240

1000

Ø 240

GABRI/ LUCIA-GD 2L
3R3.613.020

Pcs 1
Kg 5
mc 0,097

300 240

1000

Ø 240

MINIGABRI/ LUCIA-GD 1L
3R3.612.010

Pcs 1
Kg 3,5
mc 0,065

300 240

750

Ø 240

MINIGABRI/ LUCIA-GD 2L
3R3.612.020

Pcs 1
Kg 4,5
mc 0,065

300 240

750

Ø 240

COMPANY
BOLLARD
UP&DOWN
BULKHEAD
FLOODLIGHT
IN-GROUND
BRICKLIGHT
GARDEN
URBAN CLASSIC
URBAN MODERN
HIGH-BAY
POST
LAMPS
REFERENCES

REMI/LUCIA RANGE

ROUND





REMI/LUCIA E27
1R3.602.E27

Pcs 16
Kg 20
mc 0,194

4000K 3000K

REMI/LUCIA GX53

1R3.602.A1L	7W	1R3.602.A1R
1R3.602.B1L	11W	1R3.602.B1R
1R3.602.E1L	18W	1R3.602.E1R

GABRI REMI/LUCIA 1L
1R3.613.X10

Pcs 1
Kg 4,5
mc 0,097

Ø 240

GABRI REMI/LUCIA 2L
1R3.613.X20

Pcs 1
Kg 6
mc 0,097

Ø 240

MINIGABRI REMI/LUCIA 1L
1R3.612.X10

Pcs 1
Kg 3,5
mc 0,065

Ø 240

MINIGABRI REMI/LUCIA 2L
1R3.612.X20

Pcs 1
Kg 5
mc 0,065

Ø 240

REMI/LUCIA-EL E27
2R3.602.E27

Pcs 16
Kg 20
mc 0,194

4000K 3000K

REMI/LUCIA-EL GX53

2R3.602.A1L	7W	2R3.602.A1R
2R3.602.B1L	11W	2R3.602.B1R
2R3.602.E1L	18W	2R3.602.E1R

GABRI REMI/LUCIA-EL 1L
2R3.613.X10

Pcs 1
Kg 4,5
mc 0,097

Ø 240

GABRI REMI/LUCIA-EL 2L
2R3.613.X20

Pcs 1
Kg 6
mc 0,097

Ø 240

MINIGABRI REMI/LUCIA-EL 1L
2R3.612.X10

Pcs 1
Kg 3,5
mc 0,065

Ø 240

MINIGABRI REMI/LUCIA-EL 2L
2R3.612.X20

Pcs 1
Kg 5
mc 0,065

Ø 240

REMI/LUCIA-GD E27
3R3.602.E27

Pcs 16
Kg 20
mc 0,194

4000K 3000K

REMI/LUCIA-GD GX53

3R3.602.A1L	7W	3R3.602.A1R
3R3.602.B1L	11W	3R3.602.B1R
3R3.602.E1L	18W	3R3.602.E1R

GABRI REMI/LUCIA-GD 1L
3R3.613.X10

Pcs 1
Kg 4,5
mc 0,097

Ø 240

GABRI REMI/LUCIA-GD 2L
3R3.613.X20

Pcs 1
Kg 6
mc 0,097

Ø 240

MINIGABRI REMI/LUCIA-GD 1L
3R3.612.X10

Pcs 1
Kg 3,5
mc 0,065

Ø 240

MINIGABRI REMI/LUCIA-GD 2L
3R3.612.X20

Pcs 1
Kg 5
mc 0,065

Ø 240