

GERMANA

FLOODLIGHT

Rectangular floodlight with no visible screws made in shockproof resin material, UV-rays stabilized, rust and corrosion-free. Suitable for wall and post installation. Supplied with TÜV approved, long-life and efficient **GX53 LED lamps included** or provided with **E27** lampholder. Motion sensor version available. Insulation class II, Protection rating IP66.




GERMANA
2N1.000

Proiettore rettangolare senza viti a vista, fabbricato in resina antiurto stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Idoneo per installazioni a parete e a palo. Provvisto di lampadine a LED GX53 approvate TÜV di lunga durata ed elevata efficienza o fornito nella versione E27. Disponibile anche con sensore di movimento. Classe di isolamento II, grado di protezione IP66.




2N1.000.C2L



GERMANA - COMPONENTS

IP 66



COVER with no visible screws, made of shockproof resin material, UV-rays stabilized.

COVER senza viti a vista in resina antiurto stabilizzata ai raggi UV.


DIFFUSER made of UV-rays stabilized polymethylmethacrylate (PMMA) screwed to the floodlight body.

DIFFUSORE realizzato in polimetilmetacrilato (PMMA) stabilizzato ai raggi UV da avvitare al corpo del proiettore.

BODY made of shockproof resin material, UV-rays stabilized, provided with silicone rubber gasket to ensure high protection against external agents.

CORPO realizzato in resina antiurto, stabilizzata ai raggi UV, completa di guarnizione in gomma siliconica per garantire un alto livello di protezione contro gli agenti esterni.

GERMANA



280


Dimensions and weight
Height: 280 mm
Width: 180 mm
Weight: 1,4 Kg

Moulded Colours:
 Black Grey White



Diffuser PMMA:
 Opal


2x GX53 LED

FULLY PRE-WIRED



Floodlight supplied **fully pre-wired** complete with TÜV approved, long-life and efficient **2x GX53 LED lamps included**. Different wattages available. Quick and easy lamp replacement for a very simple maintenance after installation.

		*ADD. SUFFIX	
	2x 3W 6W	700 Lm	4000 K .G2L
			3000 K .G2R
	2x 7W 14W	1600 Lm	4000 K .C2L
			3000 K .C2R
	2x 10W 20W	2400 Lm	4000 K .D2L
			3000 K .D2R



2x 10W = 50W
2.400 Lm SON-HQI

SAVE 60%

E27

FULLY PRE-WIRED



Floodlight supplied **fully pre-wired** with white resin reflective ceiling designed to grant lampholder protection and isolation. Safe fixation of the electrical devices on the plate rear side.

Daylight and motion sensor available as an option. Sensor operating voltage: 220-240V (120V available on demand).

		*ADD. SUFFIX	
E27 (CFL-LED)	max 160 mm ↔	.P27	
E27 + Sensor (CFL-LED) 	max 160 mm ↔	.PS7	

POST VERSION



Detailed information on next page.


* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

LED LAMPS



More technical details about TÜV approved Fumagalli LED Lamps on page 512.





GERMANA GX53		
2N1.000.G2L	6W	2N1.000.G2R
2N1.000.C2L	14W	2N1.000.C2R
2N1.000.D2L	20W	2N1.000.D2R
4000K	2 GX53 LED LAMPS INCLUDED	3000K
Pcs 18 Kg 26,2 mc 0,198		

GERMANA E27		
E27 lampholder		2N1.000.P27
E27 with sensor		2N1.000.PS7
Pcs 18 Kg 18,1 mc 0,198		

MINIPINELA 1L		
2N1.612.010.G2L	6W	2N1.612.010.G2R
2N1.612.010.C2L	14W	2N1.612.010.C2R
2N1.612.010.D2L	20W	2N1.612.010.D2R
4000K	2 GX53 LED LAMPS INCLUDED	3000K
Pcs 1 Kg 3,5 mc 0,06		
E27 lampholder		2N1.612.010.P27
E27 with sensor		2N1.612.010.PS7

MINIPINELA 2L		
2N1.612.020.G2L	2x6W	2N1.612.020.G2R
2N1.612.020.C2L	2x14W	2N1.612.020.C2R
2N1.612.020.D2L	2x20W	2N1.612.020.D2R
4000K	2 GX53 LED LAMPS INCLUDED	3000K
Pcs 1 Kg 4 mc 0,06		
E27 lampholder		2N1.612.020.P27
E27 with sensor		2N1.612.020.PS7

PINELA 1L		
2N1.613.010.C2L	6W	2N1.613.010.G2R
2N1.613.010.D2L	14W	2N1.613.010.C2R
2N1.613.010.D2L	20W	2N1.613.010.D2R
4000K	2 GX53 LED LAMPS INCLUDED	3000K
Pcs 1 Kg 4 mc 0,097		
E27 lampholder		2N1.613.010.P27
E27 with sensor		2N1.613.010.PS7

PINELA 2L		
2N1.613.020.C2L	2x6W	2N1.613.020.G2R
2N1.613.020.D2L	2x14W	2N1.613.020.C2R
2N1.613.020.D2L	2x20W	2N1.613.020.D2R
4000K	2 GX53 LED LAMPS INCLUDED	3000K
Pcs 1 Kg 5 mc 0,097		
E27 lampholder		2N1.613.020.P27
E27 with sensor		2N1.613.020.PS7