

CECI 120

IN-GROUND



DRIVE-OVER in-ground luminaries with no visible screws, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Round or square shape available with several cover versions. Supplied as standard with TÜV approved, long-life and efficient **GX53 LED lamp 3W-350lm included**. Insulation class II, Protection rating IP67.



Apparecchio per incasso a terra CARRABILE e senza viti a vista, realizzato in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Disponibile con forma quadrata o circolare in diverse versioni di cover. Fornito con inclusa lampadina a LED GX53 3W-350lm approvata TÜV, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP67.



2F1.000.G1L



CECI 120 - COMPONENTS



IP67




COVER with no visible screws made of shockproof resin material, UV-rays stabilized, rust and corrosion free. Round or square design, 2 or 3 light versions available for a diffuse or directed light emission.



COVER senza viti a vista realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Disponibile nelle versioni quadrata o ad anello, a 2 aperture e a 3 aperture per permettere un'emissione della luce diffusa o direzionata.

DIFFUSER made of high impact and high-pressure load resistant resin material (PC), complete with silicone rubber gasket to ensure high protection against external agents. Frosted or coloured versions, to get a customized ambiance.

DIFFUSORE in resina antiurto altamente resistente al carico (PC), completo di guarnizione in gomma silconica per garantire un alto livello di protezione contro gli agenti esterni. Disponibile nella versione satinata o colorata, per ottenere un'ambientazione personalizzata.



Dimensions and weight
Installation housing depth: 93 mm
Diameter: Ø 120 mm
Weight: 0,45 Kg

Cover colours:



Diffuser PC:



HOUSING made of shockproof resin material, provided with double holes and double watertight cable glands for safe connecting cable.

CASSA realizzata in resina antiurto, provvista di doppi fori e doppio pressacavo a tenuta stagna, per consentire in maniera sicura l'ingresso e l'uscita delle connessioni elettriche.

INSTALLATION HOUSING made of shockproof resin material to be fixed into the ground before installing the luminaries.

CONTRO-CASSA in resina antiurto da fissare al suolo prima dell'installazione degli apparecchi.

GX53 LED

*ADD. SUFFIX



	3 W	350 Lm	4000 K	.G1L
			3000 K	.G1R

In-ground supplied as standard with TÜV approved, long-life and efficient **GX53 LED lamp 3W-350lm included**. Quick and easy lamp replacement for a very simple maintenance after installation.

- **COST SAVING:** long-life and efficient LED light sources
- **BUILT-IN DRIVER:** quick and easy lamp replacement
- **GREAT FLEXIBILITY:** GX53 standard lamp holder
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments.



3W 350 Lm = **40W** incandescent
SAVE 93%

LED LAMPS



More technical details about TÜV approved Fumagalli LED Lamps on page 512.

* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

CECI 120
IN-GROUND





CECI 120

2F1.000.G1L **3W** 2F1.000.G1R

4000K GX53 LED LAMP INCLUDED 3000K

Pcs 36
Kg 15,7
mc 0,084

CECI 120-3L

2F3.000.G1L **3W** 2F3.000.G1R

4000K GX53 LED LAMP INCLUDED 3000K

Pcs 36
Kg 15,7
mc 0,084

CECI 120-2L

2F2.000.G1L **3W** 2F2.000.G1R

4000K GX53 LED LAMP INCLUDED 3000K

Pcs 36
Kg 15,7
mc 0,084

CECI 120-SQ

2F4.000.G1L **3W** 2F4.000.G1R

4000K GX53 LED LAMP INCLUDED 3000K

Pcs 36
Kg 15,7
mc 0,084