

ELISA

MODERN BOLLARD




Architectural LED lamp range in modern style, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Square bollards in different sizes, spike and wall mounted versions available. Supplied with white square reflector and with TÜV approved, long-life and efficient **GX53 LED lamps included**. Insulation class II, Protection rating IP55.

*Collezione di lampade architettoniche a LED in stile moderno, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Ampia gamma di versioni disponibili per installazioni su stelo bollard in diverse altezze, con picchetto o a parete. Provvista di riflettore quadro in colore bianco e fornita con **include lampadine a LED GX53** approvate TÜV di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP55.*



DS2.564.D1L





ELISA COMPONENTS

IP55



CAP fixed to the diffuser with no visible screws made of shockproof resin material, UV-rays stabilized, rust and corrosion-free.

CALOTTA fissata al diffusore senza viti a vista, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.

DIFFUSER in clear colour made of UV-rays stabilized polymethylmethacrilate (PMMA).

DIFFUSORE trasparente realizzato in polimetilmetacrilato (PMMA) resistente all'ingiallimento ed ai raggi UV.

REFLECTOR with square shape spreading the lighting output to create a four beams luminous effect. Made of shockproof white reflective resin material.

RIFLETTORE quadro che diffonde la luce dividendola in quattro fasci. Realizzato in resina antiurto di colore bianco.



INSTALLATION ELEMENTS:

- POLES for bollard versions
- BASE for wall and surface installation
- SPIKE for in ground installation

ELEMENTI DI FISSAGGIO:

- STELI per versione bollard
- BASE per installazione a parete e al suolo
- PICCHETTO per installazione nel terreno

ELISA



Dimensions

Height: 165/500/800 mm
Width: 126 mm
Depth: 126 mm

Moulded colours:

- Black
- White
- Grey

Diffuser PMMA:

- Clear

GX53 LED



Bollard supplied with TÜV approved, long-life and efficient **GX53 LED lamp** included. Different wattages available.

			*ADD. SUFFIX	
GX53 LED	3 W	350 Lm	4000 K	.G1L
			3000 K	.G1R
GX53 LED	7 W	800 Lm	4000 K	.C1L
			3000 K	.C1R
GX53 LED	10 W	1200 Lm	4000 K	.D1L
			3000 K	.D1R



- **COST SAVING:** long-life and efficient LED light sources
- **BUILT-IN DRIVER:** quick and easy lamp replacement
- **GREAT FLEXIBILITY:** GX53 standard lamp holder
- **FUTURE-PROOFED LUMINARIES:** easy to upgrade
- **SUITABLE FOR OUTDOOR USE:** driver fully protected against heat and humidity by silicone paste.

LED LAMPS



More technical details about TÜV approved Fumagalli LED Lamps on page 512.

PHOTOMETRIC DATA SAMPLE



ELISA 800 clear GX53 10W.

Bollard height 0,8 mt
Area: 6x6 mt - average 13 lux

The photometric data for all the versions are available upon request or on our website.

3W = 40W
350 Lm incandescent
SAVE 93%

7W = 75W
10W incandescent
SAVE 90%

COMPANY BOLLARD UP&DOWN BULKHEAD FLOODLIGHT IN-GROUND BRICKLIGHT GARDEN URBAN CLASSIC URBAN MODERN HIGH-BAY POST LAMPS REFERENCES

ELISA

MODERN BOLLARD





ELISA 800		
DS2.564.G1L	3W	DS2.564.G1R
DS2.564.C1L	7W	DS2.564.C1R
DS2.564.D1L	10W	DS2.564.D1R
4000K	GX53 LED LAMP INCLUDED	3000K
Pcs 6 Kg 16 mc 0,145		

ELISA 500		
DS2.563.G1L	3W	DS2.563.G1R
DS2.563.C1L	7W	DS2.563.C1R
DS2.563.D1L	10W	DS2.563.D1R
4000K	GX53 LED LAMP INCLUDED	3000K
Pcs 12 Kg 24 mc 0,145		

ELISA WALL		
DS2.560.G1L	3W	DS2.560.G1R
DS2.560.C1L	7W	DS2.560.C1R
DS2.560.D1L	10W	DS2.560.D1R
4000K	GX53 LED LAMP INCLUDED	3000K
Pcs 18 Kg 22 mc 0,092		

ELISA SPIKE		
DS2.561.G1L	3W	DS2.561.G1R
DS2.561.C1L	7W	DS2.561.C1R
DS2.561.D1L	10W	DS2.561.D1R
4000K	GX53 LED LAMP INCLUDED	3000K
Pcs 18 Kg 23 mc 0,092		